

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

MAXELASTIC PUR



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 1 of 11

Print date: 18/10/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: MAXELASTIC PUR
UFI: 3Y61-M0CH-G00J-6Y6C

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Polyurethane coating

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **DRIZORO SAU**
Address: C/ Primavera, 50 - 52 Parque Industrial Las Monjas
City: 28850 - Torrejón de Ardoz
Province: Madrid (Spain)
Telephone: +34 91 676 66 76
Fax: +34 91 675 11 31
E-mail: info@drizoro.com
Web: www.drizoro.com

1.4 Emergency telephone number: +34 91 676 66 76 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Flam. Liq. 3 : Flammable liquid and vapour.

Skin Irrit. 2 : Causes skin irritation.

Eye Irrit. 2 : Causes serious eye irritation.

Skin Sens. 1 : May cause an allergic skin reaction.

STOT RE 2 : May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Warning

Hazard statements:

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



MAXELASTIC PUR

Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 2 of 11

Print date: 18/10/2024

P264 Wash ... thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P403+P235 Store in a well-ventilated place. Keep cool.
P370+P378 In case of fire: Use foam, carbon dioxide, sand, water spray, dry chemical, to turn it off
P501 ispose of contents / container in accordance with local legislation in force

EUH statements:

EUH208 Contains xylene. May produce an allergic reaction.
EUH208 Contains Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene. May produce an allergic reaction.

Contains:

xylene

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene	2.5 - 12.5 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 37273-56-6	[1] Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene	25 - 50 %	Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - Skin Sens. 1, H317	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 3 of 11

Print date: 18/10/2024

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Long-term chronic exposure may result in injury to certain organs or tissues.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Carbon monoxide, carbon dioxide.
- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



MAXELASTIC PUR

Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 4 of 11

Print date: 18/10/2024

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
xylene	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro-.omega.-hydroxy-, polymer with 2,4-diisocyanato-1-methylbenzene	37273-56-6	European Union [1]	Eight hours		0,06 (Calculated as NCO, skin dermal and respiratory sensitization)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

MAXELASTIC PUR



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 5 of 11

Print date: 18/10/2024

			Short term		0,012 (Calculated as NCO, skin dermal and respiratory sensitization)
--	--	--	------------	--	--

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %			
Uses:	Polyurethane coating			
Breathing protection:				
If the recommended technical measures are observed, no individual protection equipment is necessary.				
Hand protection:				
PPE:	Protective gloves.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420			
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.			
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.			
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm): 0,35
Eye protection:				
PPE:	Protective goggles with built-in frame.			
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.			
CEN standards:	EN 165, EN 166, EN 167, EN 168			
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.			
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.			
Skin protection:				
PPE:	Protective clothing.			
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.			
CEN standards:	EN 340			
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.			
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.			
PPE:	Work footwear.			
Characteristics:	«CE» marking, category II.			
CEN standards:	EN ISO 13287, EN 20347			

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 6 of 11

Print date: 18/10/2024

Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: MULTICOLOR

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not available

Melting point: Not applicable

Freezing point: Not applicable

Boiling point or initial boiling point and boiling range: >100 °C

Flammability: Not available

Lower explosion limit: Not available

Upper explosion limit: Not available

Flash point: 30 °C

Auto-ignition temperature: Not available

Decomposition temperature: Not available

pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not available

Solubility: Not available

Hydrosolubility: Not applicable

Liposolubility: Not available

Partition coefficient n-octanol/water (log value): Not available

Vapour pressure: Not available

Absolute density: Not available

Relative density: 1.40

Relative vapour density: Not available

Particle characteristics: Not applicable

9.2 Other information

Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

MAXELASTIC PUR



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 7 of 11

Print date: 18/10/2024

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
xylene CAS No: 1330-20-7 EC No: 215-535-7	Oral	LD50	Rat	4300 mg/kg bw [1]
		[1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956		
	Dermal	LD50	Rabbit	> 1700 mg/kg bw [1]
		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974		
	Inhalation	LC50	Rat	21,7 mg/l/4 h [1]
		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974		

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 11.000 mg/kg

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Product classified:

Specific target organ toxicity following a repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure.

j) aspiration hazard;

Not conclusive data for classification.

11.2 Information on other hazards.

Endocrine disrupting properties

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



MAXELASTIC PUR

Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 8 of 11

Print date: 18/10/2024

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
xylene	Fish	LC50	Fish	15,7 mg/l (96 h) [1]
		[1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212		
	Aquatic invertebrates	LC50	Crustacean	8,5 mg/l (48 h) [1]
		[1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p		
CAS No: 1330-20-7 EC No: 215-535-7	Aquatic plants			

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

MAXELASTIC PUR



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 9 of 11

Print date: 18/10/2024

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1139

14.2 UN proper shipping name.

Description:

ADR/RID: UN 1139, COATING SOLUTION, 3, PG III, (D/E)

IMDG: UN 1139, COATING SOLUTION, 3, PG III (30°C)

ICAO/IATA: UN 1139, COATING SOLUTION, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

Transport by ship, FEM – Emergency sheets (F – Fire, S - Spills): F-E, S-E

14.6 Special precautions for user.

Labels: 3



Hazard number: 30

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

VOC content (p/p): 0 %

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



MAXELASTIC PUR

Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 10 of 11

Print date: 18/10/2024

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Resp. Sens. 1 : Respiratory sensitiser, Category 1
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1

Changes regarding to the previous version:

- Changes in the information of the supplier (SECTION 1.3).
- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the first aid measures (SECTION 4.1).
- Modification of the symptoms (SECTION 4.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Addition of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Modification of the information of the stability and reactivity conditions (SECTION 10.1).
- Modification of the information of the stability and reactivity conditions (SECTION 10.4).
- Modification of the information of the stability and reactivity conditions (SECTION 10.5).
- Modification of the information of the stability and reactivity conditions (SECTION 10.6).
- Change in the hazard classification (SECTION 11.1).
- National legislative changes (SECTION 15.1).
- Elimination of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

MAXELASTIC PUR



Version 1 Date of compilation: 18/10/2024

Version 4 (replaces version 3)

Revision date: 18/10/2024

Page 11 of 11


Print date: 18/10/2024

Environmental hazards

Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Risk classification system NFPA 704:



Health hazard: 2 (Hazardous)

Flammability: 3 (Below 100°F)

Reactivity: 0 (Stable)

Abbreviations and acronyms used:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.